


PCT/2009/0068607

REC'D	12 NOV 1999
WIPO	PCT

4 #6/PP
10/17/01

PA 156375



THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

October 04, 1999

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 09/169,395

FILING DATE: October 09, 1998

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED
BUT NOT IN COMPLIANCE WITH
RULE 17.1(a) OR (b)



By Authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS

H. L. Jackson

H. L. JACKSON
Certifying Officer

16533 U.S. PRO

U.S. PTO

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re Application Of:
Dr. Frederick J. Bruwer

Serial No.:

Filed:

Title: INTELLIGENT ELECTRICAL DEVICES COMPRISING MICROCHIPS

www.ck12.org

Group Art #:

Examiner:

Docket #: B71403US

Jc551 U.S. PTO

09/169395



10/09/98

Assistant Commissioner for Patents
Box New Application
Washington, D.C. 20231

CERTIFICATE OF MAILING BY EXPRESS MAIL
I hereby certify that this correspondence is being deposited with the United State Postal Service as Express Mail (Label #EE667576502US) in an envelope addressed to Assistant Commissioner for Patents, Box New Application, Washington, DC 20231

Debbie Allen
Debbie Allen

Debbie Allen
October 9, 1998
Date

Dear Sir:

TRANSMITTAL LETTER

Applicant, Dr. Frederick J. Bruwer, hereby submit the following documents to be filed with the United States Patent and Trademark Office:

1. Patent Application, including 33 pages of specification, 40 claims and 18 drawing sheets;
2. Check in the amount of \$1,558.00 for filing application;
3. Return postcard.

Please debit our account no. 02-0840 for any underpayment or credit the account for any overpayment of fees due in this case.

Date:

10/9/98

Respectfully submitted,

Bruce W. Slayden/1

Reg. No. 33,790

Attorney for Applicant

FROHWITTER LAW FIRM

Three Riverway, Suite 500

Houston, Texas 77056

Tel: (713) 621-0703

Fax: (713) 622-1624

INTELLIGENT ELECTRICAL DEVICES COMPRISING
MICROCHIPS

Invented

by

Dr. Frederick Bruwer

Bruce W. Slayden II
Reg. No. 33,790
Frohwitter Law Firm
Three Riverway
Suite 500
Houston, Texas 77056
Tel: (713) 621-0703
Fax: (713) 622-1624

866001-5669160

FIELD OF THE INVENTION

The present invention relates to new intelligent electrical current switching devices and more particularly, to microchip controlled electrical current switching devices. The invention further relates, in one embodiment, to intelligent batteries having embedded therein a microchip for use with a variety of electrical devices to add heretofore unknown functionality to existing electrical devices. The invention also relates, according to another embodiment, to intelligent hand-held electronic devices, and in a preferred embodiment to hand-held light sources, and more particularly, to flashlights. According to one embodiment of the present invention, the invention relates to intelligent hand-held flashlights having microchip controlled switches wherein said switches can be programmed to perform a variety of functions including, for example, turning the flashlight off after a pre-determined time interval, blinking, or dimming, etc. According to a still further embodiment, the invention relates to low current switches controlled by microchips of the present invention for use in building lighting systems.

BACKGROUND OF THE INVENTION

In conventional flashlights, manually-operated mechanical switches function to turn the flashlight "on" and "off." When turned "on," battery power is applied through the closed switch to a light bulb, the amount of power then consumed depends on how long the switch is closed. In the typical flashlight, the effective life of the battery is only a few hours at most. Should the operator, after using the flashlight to find his/her way in the dark or for any other purpose, then fail to turn it off, the batteries will, in a very short time, become exhausted. Should the flashlight be left in a turned-on and exhausted

866001-5669160

condition for a prolonged period, the batteries may then leak and exude corrosive electrolyte that is damaging to the contact which engages the battery terminal as well as the casing of the flashlight.

When the flashlight is designed for use by a young child the likelihood is greater that the flashlight will be mishandled, because a young child is prone to be careless and forgets to turn the flashlight "off" after it has served its purpose. Because of this, a flashlight may be left "on" for days, if not weeks, and as a result of internal corrosion may no longer be in working order when the exhausted batteries are replaced.

Flashlights designed for young children are sometimes in a lantern format, with a casing made of strong plastic material that is virtually unbreakable, the light bulb being mounted within a reflector at the front end of the casing and being covered by a lens from which a light beam is projected. A U-shaped handle is attached to the upper end of the casing, with mechanical on-off slide switch being mounted on the handle, so that a child grasping the handle can readily manipulate the slide actuator with his/her thumb.

With a switch of this type on top of a flashlight handle, when the slide actuator is pushed forward by the thumb, the switch "mechanically" closes the circuit and the flashlight is turned "on" and remains "on" until the slide actuator is pulled back to the "off" position and the circuit is opened. It is this type of switch in the hands of a child that is most likely to be inadvertently left "on."

To avoid this problem, many flashlights include, in addition to a slide switch, a push button switch which keeps the flashlight turned on only when finger pressure is applied to the push button. It is difficult for a young child who wishes, say to illuminate

a dark corner in the basement of his home for about 30 seconds, to keep a push button depressed for this period. It is therefore more likely that the child will actuate the slide switch to its permanently-on position, for this requires only a monetary finger motion.

It is known to provide a flashlight with a delayed action switch which automatically turns off after a pre-determined interval. The Mallory U.S. Patent No. 3,535,282 discloses a flashlight that is automatically turned off by a delayed action mechanical switch assembly that includes a compression spring housed in a bellows having a leaky valve, so that when a switch is turned on manually, this action serves to mechanically compress the bellows which after a pre-determined interval acts to turn off the switch.

A similar delayed action is obtained in a flashlight for children marketed by Playskool Company, this delayed action being realized by a resistance-capacitance timing network which applies a bias to a solid-state transistor switch after 30 seconds or so to cut off the transistor and shut off the flashlight. Also included in the prior art, is a flashlight previously sold by Fisher-Price using an electronic timing circuit to simply turn off the flashlight after about 20 minutes.

It is also known, *e.g.* as disclosed in U.S. Patent No. 4,875,147, to provide a mechanical switch assembly for a flashlight which includes a suction cup as a delayed action element whereby the flashlight, when momentarily actuated by an operator, functions to connect a battery power supply to a light bulb, and which maintains this connection for a pre-determined interval determined by the memory characteristics of the suction cup, after which the connection is automatically broken.

U.S. Patent No. 5,138,538 discloses a flashlight having the usual components of a battery, and on-off mechanical switch, a bulb, and a hand-held housing, to which there is added a timing means and a circuit-breaking means responsive to the timing means for cutting off the flow of current to the bulb, which further has a by-pass means, preferably child-proof, to direct electric current to the light bulb regardless of the state of the timing means. The patent also provides for the operation of the device may be further enhanced by making the by-pass means a mechanical switch connected so as to leave it in series with the mechanical on-off switch. Furthermore, the patent discloses a lock or other "child-proofing" mechanism may be provided to ensure that the by-pass is disabled when the flashlight is switched off.

Most conventional flashlights, like those described above, are actuated by mechanical push or slide button-type switches requiring, of course, mechanical implementation by an operator. Over time, the switch suffers "wear and tear" which impairs operation of the flashlight as a result of, for example, repeated activations by the operator and/or due to the fact that the switch has been left "on" for a prolonged period of time. In addition, such mechanical switches are vulnerable to the effects of corrosion and oxidation and can cause said switches to deteriorate and to become non-functioning. In addition, these prior art devices having these mechanical switches are generally "dumb," *i.e.* they do not provide the user with convenient, reliable, and affordable functionalities which today's consumers now demand and expect.

~~The prior art switches typically provide two basic functions in prior art flashlights.~~

First, the mechanical switches act as actual conductors for completing power circuits and

providing current during operation of the devices. Depending upon the type of bulb and wiring employed, the intensity of electrical current which must be conducted by the switch is generally quite high leading to, after prolonged use, failure. Second, these mechanical switches must function as an interface between the device and its operator, *i.e.* the man-machine-interface ("MMI") and necessarily requires repeated mechanical activations of the switch which over time mechanically deteriorate.

Also, currently the electrical switches used in buildings/houses for control of lighting systems are of the conventional type of switches which must conduct, *i.e.* close the circuit, upon command, thus also providing the MMI. These prior art switches suffer from the same disadvantages as the switches described above in relation to portable electronic devices, like flashlights. Moreover, the switches are relatively dumb in most cases and do not provide the user with a variety of functions, *e.g.* but not limited to timing means to enable a user, for example, a shop owner or home owner to designate a predetermined shut off or turn on point in time.

There is a need for inexpensive, reliable, and simple intelligent electronic devices which provide increased functionality and energy conservation.

SUMMARY OF THE INVENTION

According to one embodiment of the present invention, there is provided a microchip controlled switch to manage both the current conducting functions and the MMI functions in an electronic device, such as a flashlight, on a low current basis *i.e.* without the MMI device having to conduct or switch high current. According to one aspect of

the invention, the MMI functions are controlled by very low current signals, using touch pads, or carbon coated membrane type switches. These low current signal switches of the present invention can be smaller, more reliable, less costly, easier to seal and less vulnerable to the effects of corrosion and oxidation. Moreover, since the switch is a solid state component, it is, according to the present invention, possible to control the functions of the device in an intelligent manner by the same microchip which provides the MMI functions. Thus, by practicing the teachings of the present invention, more reliable, intelligent, and efficient electrical devices can be obtained which are cheaper and easier to manufacture than prior art devices.

According to another embodiment of the invention, there is provided a microchip which can be embedded in a battery that will lend intelligence to the battery and thus, the device it is inserted into, so that many functions, including but not limited to, delayed switching, dimming, automatic shut off, and intermittent activation may be inexpensively realized in an existing (nonintelligent) product, for example a prior art flashlight.

According to a further embodiment, the invention provides a power saving microchip which, when operatively associated with an electronic device, will adjust the average electric current through a current switch, provide an on and off sequence which, for example, but not limited to, in the case of a flashlight, can be determined by an operator and may represent either a flash code sequence or a simple on/off oscillation, provide an indication of battery strength, and/or provide a gradual oscillating current flow to lengthen the life of the operating switch and the power source.

09169395-100998

According to one embodiment of the invention, an intelligent flashlight, having a microchip controlled switch is provided comprising a microchip for controlling the on/off function and at least one other function of the flashlight. According to a further embodiment of the invention, an intelligent flashlight having a microchip controlled switch is provided comprising an input means for sending activating/deactivating signals to the microchip, and a microchip for controlling the on/off function and at least one other function of the flashlight. According to a further embodiment of the invention, there is provided an intelligent flashlight having a microchip controlled switch comprising an input means for selecting one function of the flashlight, a microchip for controlling at least the on/off function and one other function of the flashlight, wherein the microchip control circuit may further comprise a control-reset means, a clock means, a current switch, and/or any one or combination of the same.

According to another embodiment of the invention, there is provided a battery for use with an electrical device comprising a microchip embedded in the battery. According to still a further embodiment of the invention, a battery for use with an electronic device is provided comprising a microchip embedded in the battery wherein said microchip is adapted such that an input means external to the microchip can select the on/off function and at least one other function of the electronic device.

According to one embodiment of the present invention, there is provided an intelligent battery for use with an electronic device, the battery having positive and negative terminal ends and comprising a microchip embedded in the battery, preferably in

the positive terminal end, for controlling on/off functions and at least one other function of the electronic device.

According to another embodiment of the invention, there is provided a portable microchip device for use in serial connection with a power source, *e.g.* an exhaustible power source, and an electronic device powered by said source wherein said electronic device has an input means for activating and deactivating said power source, and said microchip comprising a means for controlling the on/off function and at least one other function of the electronic device upon receipt of a signal from said input means through said power source.

According to a still further embodiment of the invention, there is provided a microchip adapted to control lighting in buildings. According to this embodiment, the normal switch on the wall that currently functions as both a power-switch, *i.e.* conduction of electricity, and MMI can be eliminated, thus eliminating the normal high voltage and high current dangerous wiring to the switch and from the switch to the load or light. Utilizing the present invention, these switches can be replaced with connecting means suitable for low current DC requirements.

According to another embodiment, the present invention is directed to a battery comprising an energy storage section, a processor, *e.g.* a microchip and first and second terminal ends. The first terminal end being connected to the energy storage section, the second terminal end being connected to the processor, and the processor being connected to the second terminal end and the energy storage section. ~~The processor controls the connection of the second terminal end to the energy storage section.~~

According to another embodiment, the present invention provides an electronic apparatus which includes an electrical device, comprising a power supply, an activating/deactivating means, and a processor. The activating/deactivating means is connected to the processor and the processor is connected to the power supply. The processor controls the on/off function of the device and at least one other function of the device in response to signals received from the activation/deactivation means.

The present invention, according to a still further embodiment, provides a flashlight comprising a light source, an energy storage means, a switch means, and a processor means. The switch means being in communication with the processor means and the processor means being in communication with the energy storage means which is ultimately in communication with the light source. The processor controls the activation/deactivation of the light source and, in some embodiments, further functions of the flashlight, in response to signals received from the switch means.

While the present invention is primarily described in this application with respect to either a flashlight or a battery therefore, the embodiments discussed herein should not be considered limitative of the invention, and many other variations of the use of the intelligent devices of the present invention will be obvious to one of ordinary skill in the art.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a schematic of a device having a microchip controlled push button or sliding type input activation/deactivation switch according to one embodiment of the present invention;

Figure 2 is a block diagram of a microchip for use in association with a push button or sliding input activation/deactivation switch according to one embodiment of the invention;

Figure 3 is a schematic of a second type of intelligent device having a microchip controlled push button or sliding type input activation/deactivation switch according to another embodiment of the invention;

Figure 4 is a schematic of a device having a microchip controlled touch pad or carbon coated membrane activation/deactivation switch according to a still further embodiment of the invention;

Figure 5 is a block diagram of a microchip for use in association with a touch pad or carbon coated membrane activation/deactivation switch according to one embodiment of the invention;

Figure 6 is a schematic of a second type of device having a microchip controlled touch pad or carbon coated membrane activation/deactivation switch according to one embodiment of the invention;

Figure 7 is a schematic of a battery having embedded therein a microchip according to a further embodiment of the invention;

Figure 8A is a block diagram of a microchip for use in a battery according to one embodiment of the present invention;

Figure 8B is a block diagram of a second type of microchip for use in a battery according to another embodiment of the present invention;

Figure 9 is a schematic of a device having a microchip controlled switch according to one embodiment of the invention;

Figure 10 is a schematic of a device having a microchip controlled switch according to one embodiment of the invention;

Figure 11 is a schematic of a device having a microchip controlled switch according to one embodiment of the present invention;

Figure 12 is a schematic of a flashlight having therein a microchip controlled switch according to one embodiment of the present invention;

Figure 13 illustrates a possible position, according to one embodiment of the present invention of a microchip in a battery;

Figure 13b illustrates one embodiment of the present invention wherein a microchip is in single wire connection to the battery cells inside the battery (a virtual or ground reference level will have to be created and is not shown);

Figure 13c illustrates one embodiment of the present invention wherein a microchip is in a two wire connection to the cells within the battery (a power or ground reference can be obtained from the cells);

Figure 14 is a schematic of one embodiment of the present invention of a low current switching device suitable for lighting systems in buildings;

Figure 15 is a block diagram of one embodiment of the present invention, *i.e.* microchip 1403 of Figure 14;

Figure 16 is a flow diagram for a microchip as shown in Figures 4 and 5 for a delayed shut off function embodiment of one embodiment of the present invention; and

Figure 17 is a flow diagram for a microchip as shown in Figures 7 and 8a for a delayed shut off function embodiment of one embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

According to one embodiment or aspect of the present invention, and referring to Figure 1, a schematic depiction of main circuit 100 of an electronic device, for example, a flashlight, is provided, wherein the device has a microchip 103 and a microchip controlled input activator/deactivator 102, for example, a push button or sliding switch. Main circuit 100 of the device is powered by a current supplied by power source 101. Power source 101 may be any power source, e.g. a DC battery, as is well known to those of ordinary skill in the art. While the following discussion is limited to specific electronic devices, that is flashlights, it is to be understood that the following description is equally applicable to other electronic devices including portable radios, toys, for example but not limited to battery operated cars, boats, planes, and/or other electrically powered toys.

Referring to Figure 1, when an operator activates input push button or sliding command switch 102 to the "on" position, the microchip 103 receives a signal. Switch 102 is a direct electrical input to microchip 103. Microchip 103 is grounded by grounding means 104. Microchip 103 is in series between power source 101 and load 105. Microchip 103 also transfers sufficient power through means of a current switch (not shown in Figure 1) to load 105 which can be, for example, a resistor-type bulb in the case of a flashlight to provide illumination.

09169395-100998

The microchip 103, and other microchips of the present invention, can have its/their intelligence embedded in combinational or sequential logic, a PLA or ROM type structure feeding into a state machine or a true microcontroller type structure. The memory for the above will normally be non-volatile, but should there be a need for selectable options, EE or flash memory structures may be used.

The structure and operational parameters of such a microchip 103 are explained in greater detail below with respect to Figure 2. As shown in Figure 1, power is supplied to microchip 103 by power source 101. When an operator activates input switch 102 to the "on" position it represents a command which is communicated to microchip 103. Input means 102 requires very low current in preferred embodiments. In one embodiment of the invention, microchip control/reset means 201 simply allows the current switch 202 to pass current provided from power source 101 to load 105 in an unimpeded manner when the MMI switch 102 is activated, and, in the case of a flashlight, illumination is obtained. It is important to recognize, however, that it is control circuit 201 which activates current switch 202 upon acting on an input from MMI switch 102. Unlike heretofore known prior art devices, activating switch 102 does not conduct current to load 105, but is only a command input mechanism which can, according to the invention, operate on very low current. For example, according to the invention, touch sensor input or carbon coated membrane type switch devices are preferred.

If, for example, an emergency notification function is desired, the flashlight may be designed to alternately flash on and off every second. First, the operator activates input 102 into the appropriate position to indicate such a function is desired. During the "on"

segment of the flashing routine, control/reset means 201 commands current switch 202 to close and let current flow through to load 105, thereby causing, in the case of a flashlight, the bulb to illuminate. Simultaneously, control/reset means 201 uses the timing means 203 as a clock for timing. After control/reset means 201 determines one second has elapsed, control/reset means 201 instructs current switch 202 to open and interrupt the current flow through to load 105, and bulb illumination is discontinued. It is important to note that both control/reset means 201 and current switch 202 are still active and fully powered; however, current delivery is now latent with respect to load 105. When another second has elapsed, a command is passed from control/reset means 201 which again allows current to be delivered through current switch 202 to load 105, and in the case of a flashlight, bulb illumination is immediately resumed. The device continues an alternating current delivery routine until either the operator switches the setting of the activating input switch 102 to the "off" position, or until the conditions pre-programmed into the microchip, *e.g.* into the control/reset means 201, are satisfied and current delivery is permanently discontinued.

Similar operating routines can be employed to generate other conspicuous flashing functions such as the generation of the universal distress signal S.O.S. in Morse code. Again, such a function would require that the microchip, *e.g.* control/reset means 201, be pre-programmed with the appropriate code for creating such a signal, and to permit current transmission from switch 202 to load 105 in accordance with the code with the assistance of timing means 203. For example, it may be desirable to have an S.O.S. sequence wherein flashes representing each individual letter are separated by time intervals ranging

from one-half (1/2) second to one (1) full second, while the interval between each letter in the code comprises two (2) full seconds. After a certain number of repetitions of the routine, again determined by the operator or as pre-programmed within the microchip, *e.g.* within the control/reset means 201, the signal is discontinued.

As shown in Figure 3, it is possible to remove grounding means 104 from main circuit 100. However, it is then necessary to intermittently provide an alternative power source for microchip 103 and to create a virtual ground reference level. A suitable microchip 103 for this configuration is described in greater detail below with respect to Figures 8A and 8B.

Referring now to Figure 4, utilizing the circuits in the microchip of some embodiments of the present invention, carbon coated membrane or touch pad type switches are preferred. Carbon coated membrane switches and touch pad switches have many advantages over conventional high current switches, such as those currently used in flashlights. According to the present invention, carbon coated membrane type switches, low current type switches, and touch pad type switches can be used which may be smaller, less costly, easier to seal, and less vulnerable to corrosion and oxidation than conventional switches which also transfer energy or current to the load. Moreover, according to one embodiment of the present invention, carbon coated membrane type switches, touch pad switches, or low current type switches can be formed structurally integral with the product, for example, with the casing of a flashlight.

A block diagram showing microchip 103 for use, in accordance with one embodiment of the present invention, in association with a carbon coated membrane, a touch pad

switch, or a low current type switch 106 is now explained in greater detail in respect to Figure 5. According to this one embodiment of the present invention, current switch 202 is powered directly by grounded power source 101. However, output of current from current switch 202 to load 105 is dependent on control/reset means 201. When an operator depresses touch pad 106, carbon coated membrane switch 106 or low current type switch 106, control/reset means 201 allows current switch 202 to flow current through to load 105. However, in more intelligent applications according to certain embodiments of the present invention, control/reset means 201 will coordinate, based on clock and/or timing means 203, to execute timing routines similar to those described above such as, but not limited to, intermittent flashing, the flashing of a conspicuous pattern such as Morse code, dimming functions, battery maintenance, battery strength/level, etc.

As shown in Figure 6, grounding means 104 can be removed from the system as a matter of design choice. A more detailed description of a suitable microchip 103 for this type of configuration is provided below with respect to Figures 8A and 8B.

Referring to Figure 7, certain embodiments of the present invention also provide for a battery having a microchip embedded for use in association with an electronic device. As shown, direct current is provided to microchip 103 by power source 101. When activating input switch 102 is closed, current is complete and power is transferred to load 105 at the direction of microchip 103. Microchip 103 embedded in the battery can have any number of intelligent functions pre-programmed therein, such as, for example but not limited to, battery strength monitoring, recharging, adjustment of average current through a current switch, intermittent power delivery sequences, and so on. Examples of suitable

microchips 103 for this type of application are discussed below with reference to Figures 8A and 8B.

Figures 8A and 8B are block diagrams of two different further embodiments of the present invention. Microchip 803 is especially suitable for applications wherein microchip 803 is not grounded through the body of the electrical device or where a ground cannot otherwise be established because of design considerations. This embodiment is useful to provide sufficient operating power to the microchip and can be achieved by periodically opening and closing current switch 202 when activation input switch 102 is closed. For example, referring to Figure 8A, when input switch 102 is closed but current switch 202 does not conduct (that is, the switch is open and does not allow current to flow to load 105), then voltage drop over load 105 is zero and in the case of a flashlight, no illumination is provided from the bulb. Instead, the full voltage drop is over current switch 202 and in parallel with the diode 204 and capacitor 205. Once capacitor 205 becomes fully charged, current switch 202 can close and circuit 103 will be powered by capacitor 205. When circuit 803 is adequately powered, it functions in a manner identical to the circuits described previously with respect to the functions provided by control/reset means 201 and timing means 203.

When the charging capacitor 205 starts to become depleted, control/reset means 201 will recognize this state and reopen the current switch 203, thus briefly prohibiting the flow of current to load 105, in order to remove the voltage drop from load 105 and allow capacitor 205 to recharge and begin a new cycle. In a flashlight application, the time period wherein current flow from current switch 202 is discontinued can be such that

the dead period of the light is not easily or not at all detectable by the human eye. In the case of a high current usage load, such as a flashlight, it means the ratio of the capacitance of the capacitor having to power the microchip and the current consumption of the microchip, must be such that the capacitor can power the microchip for a long time relative to the charging time (202 open). This will enable the flashlight's "off" time to be short and the "on" time to be long, thus not creating a detectable or intrusive switching of the flashlight to the user.

According to another embodiment of the present invention, *e.g.* in relation to another product of low current consumption, such as a FM radio, the designer may opt for a capacitive (reservoir) device externally to the microchip (see FIG. 11). In this case, the electrical device may function for a time longer than the time required for charging the capacitor (205, 207) which is when the current switch (202) is open and not conducting current.

According to another embodiment of the present invention, an output may be provided to indicate a condition, *e.g.* a battery is in good or bad condition. It may also be suitable to assist in locating a device, *e.g.* but not limited to a flashlight, in the dark. This may be a separate output pin or may be, according to another embodiment, shared with the MMI switch input. (See FIG. 11) This output or indicator may be a LED. Referring to Figure 11, indicator/output device 1104 may, for example, be an LED. When microchip 1113 pulls the line 1114 to high, the LED 1104 shines. LED 1104 may also shine when switch 1111 is closed by the user. However, since that is only a momentary closure, this should not create a problem.

According to a further specific embodiment of the invention, referring to Figure 11, microchip 1113 can activate the LED 1104 for a short time, *e.g.* every 100 milliseconds, every 10 seconds. This indication will let potential users know the device is in a good state of functionality and will enable fast location of the device in the dark, *e.g.* in times of emergency. The low duty cycle will also prevent unnecessary battery depletion.

With an alternative embodiment of the present invention, Figure 8B illustrates the charging and discharging of capacitor 207 to provide power to circuit 803, wherein the diode and capacitor structure establishes a ground reference for circuit 803.

Each of the embodiments explained with respect to Figures 8A and 8B are suitable for use, according to the present invention, depending upon the application. Indeed, the embodiments shown in Figures 8A and 8B can be directly embedded into a battery and/or can be separately constructed in another portable structure, *e.g.* but not limited to, in the shape of a disc, about the size of a quarter, to be inserted at the end of the battery between the output means or positive terminal of the battery and the current receiving structure of the electronic device. As described, the embodiments shown in Figures 8A and 8B can be utilized with the prior art high current switches currently being utilized in simple non-intelligent electronic devices, for example flashlights, radios and toys. For example, in the case of a portable simple radio without any intelligence, an automatic shut "off" may be achieved by using the intelligent battery or portable microchip of the present invention having a timing function to automatically shut off the radio after a given period of time, *i.e.* after the user is asleep.

09169395-100998

The architecture of the two embodiments of the present invention shown in Figures 8A and 8B provide certain advantages over the simple dumb architecture in current simple electrical devices, for example, flashlights. Due to the unique design of the microchips, as shown in Figures 8A and 8B, after the device (into which the microchip is incorporated) is shut off the microchip remains powered for an additional period of time which allows for said microchip to thus receive additional commands, for example, a second "on" activation within a given period after a first "on" and "off" activation, may be programmed into the microchip (control/reset means) to indicate a power reduction or dimming function or any other function as desired by the designer of said device. This is accomplished by the inventive designs of the present invention without having to utilize substantial energy from what are typically small exhaustible power sources, *e.g.* DC batteries in the case of flashlights.

According to some embodiments of the present invention, more intelligent devices include many other useful functions pre-programmed within the microchip, *e.g.* in control/reset means 201 and may, *e.g.* be assisted by a timing means 203. Referring to Figure 2, commands can be entered through switch 102 in several different ways. First, various time sequences of closed and open activations may represent different commands. For example, but not limited to, a single closure may instruct microchip 103 to activate current switch 202 continuously for a pre-determined length of time. Alternatively, two successive closures may instruct the microchip 103 to intermittently activate current switch 202 for a pre-determined length of time and sequence, for example, a S.O.S. sequence.

Secondly, referring to Figure 9, commands may be communicated to microchip 903 through the use of various voltages recognizable by microchip 903 to represent various commands. For example, but not limited to, according to one embodiment of the present invention, it may include multiple activating switches 901 and 902 connecting different voltages to the command input structure of microchip 903.

Thirdly, referring to Figure 10, commands may be communicated to microchip 1103 through the use of multiple specific switches (1004, 1005, 1006, 1007) which when activated either singularly or in combination is/are recognizable by microchip 1103 as representing various different commands.

As can be seen by Figure 9, switch 901 and 902 and in Figure 10, switches 1004, 1005, 1006, and 1007, power or ground may be used as a command reference voltage level. For example, the switches in Figure 10 may be connected to another ground instead of point 1008 depending on the internal structure of the microchip.

The control/reset means included in the inventive microchips of the present invention may and in some instances, depending upon the application, should in addition to the many possible user functions described above, include means for adjusting the average current over a switch and/or a means for providing a gradual "on"/"off" current flow, so that the operator does not appreciably perceive the increase and decrease in light provided by the device. These features allow for an ongoing variable level of lighting as desired by an operator, and may also lengthen the life span of the activation switch, the bulb, and the power source. Moreover, several functions can now be added to an existing

device, like a flashlight, through the use of a battery having embedded therein a microchip according to the present invention.

In another embodiment of the invention, the microchip is adapted to control lighting in buildings. The normal switch on the wall that currently functions as both a power-switch and MMI can be replaced by a low current switching device like a membrane switch, touch pad or carbon coated switching device. Since very low currents are required by the MMI switch (device) that replaces the normal wall mounted (A/C) switch, it is possible to replace the normal high voltage/current (dangerous) wiring to the switch and from the switch to the load (light), with connectivity means suitable to the new low current DC requirements. As such, in the case of normal A/C wiring (110V/220V), the dangerous wiring can now be restricted to the roof or ceiling and all switches (MMI's) can inherently be safe. This may make the expensive and regulated safety piping required for the wiring of electricity to wall switches redundant.

In a specific embodiment, the traditional wiring between the light and the wall switch is replaced by flexible current conducting tape that can be taped from the roof and down the wall to the required location. In another embodiment, the connections can be made by current conducting paint or similar substances. In both cases above, it can be painted over with normal paint to conceal it. This makes changing the location of a wall switch or the addition of another switch very easy.

The microchip according to the present invention can be located in the power fitting of the light. The microchip having the low current (MMI) input and a power switch to block or transfer the energy to the load (light, fan, air conditioner). It reacts

to the inputs received to activate or disable, or control other functions, of whatever device it is controlling.

The microchip may be adapted to contain the high current/voltage switch or control an external switching device or relay. The microchip may also, as in the other embodiments discussed, have some intelligence to control functions like dimming, delayed shut off, timed activation/deactivation, timed cycles, flashing sequences and gradual on/off switching. The microchip may also be adopted, as in a specific flashlight embodiment discussed, to provide a location/emergency signal for lighting/flashing an LED.

The power input 101 in Figure 14 may be DC (eg 12V) as is commonly used for some lights or A/C (110V or 240V). The device shown as 1403 may be monolithic or be a multichip unit having a relay (solid state or mechanical), a regulator (eg: 110AC volt to 12V DC) and a microchip as discussed in this application.

In a specific embodiment, Ic pin 1406 can normally be high and a closure of input means 1402, *e.g.* any of the low current switching devices described above, can be detected as Ic pin 1405 also goes too high. To flash the LED 1404 the microchip will reverse the polarities so that Ic pin 1405 becomes high with regards to Ic pin 1406. During this time, it may not be possible to monitor the closure of the input 1402 switch and the LED 1404 may not shine should the input 1402 be closed. In another embodiment, microchip 1403 is able to detect closure of input 1402 before reversing the voltage polarity as discussed and if it detects closure, it does not proceed with reversing the polarity.

In Figure 15, microchip 1503 does not contain a current switch (eg switch 102) as shown in Figure 2. However, if desired the regulator and relay can be integrated into a single monolithic microchip 1503. In case of a 12V (DC) local voltage this may be done in any event unless the current/power considerations is too high to make it practical.

In another embodiment, the microchips 1403 and 1503 are adapted to receive commands not only via the MMI input but also over the load power (electricity) wiring. This would allow a central controller to send out various commands to various power points, controlled by a microchip according to this invention, by using address information of specific microchips or using global (to all) commands.

While the preferred embodiments of the present invention have been described in detail, it will be appreciated by those of ordinary skill in the art that changes and modifications may be made to said embodiments without, however, departing from the spirit and scope of the present invention as claimed.

I claim:

1. An intelligent flashlight having an exhaustible power source, said flashlight comprising:

at least one non-energy transferring MMI signal switch and a microchip in communication with said switch,

the switch being capable of only transmitting a signal to said microchip that the switch has been activated or deactivated by a user, and

the microchip being in communication with the power source and controlling the on/off functions and at least one other function of the device in response to the receipt of activation and deactivation signals from the switch.

2. The intelligent flashlight of claim 1, wherein the switch is structurally integral with the microchip and adapted for single wire input operation.

3. The intelligent flashlight of claim 1, wherein the switch comprises a carbon coated membrane interface.

4. The intelligent flashlight of claim 1, wherein the switch comprises a touch pad interface.

5. The intelligent flashlight of claim 1, wherein the microchip comprises a control/reset means.

6. The intelligent flashlight of claim 1, wherein the microchip comprises a timing means.

7. The intelligent flashlight of claim 1, wherein the at least one other function controlled by the microchip is a delayed shut off function.

8. The intelligent flashlight of claim 1, wherein the at least one other function controlled by the microchip is an average current adjustment function.

9. The intelligent flashlight of claim 1, wherein the at least one other function controlled by the microchip is a power reduction function.

10. The intelligent flashlight of claim 1, wherein the at least one other function controlled by the microchip is an oscillating power function.

11. The intelligent flashlight of claim 1, wherein the at least one other function controlled by the microchip is an intermittent code sequence function.

12. The intelligent flashlight of claim 1, wherein the at least one other function controlled by the microchip is a determination of the charge remaining in the power source-function.

13. The intelligent flashlight of claim 12, wherein the microchip is in communication with a means for indicating to an operator the charge remaining in the power source.

14. The intelligent flashlight of claim 1, wherein the microchip recognizes that a number of successive activations/deactivations signals received from the signal switch corresponds to a particular specific at least one other function.

15. The intelligent flashlight of claim 1, wherein the microchip recognizes that the receipt of different voltages from the signal switch corresponds to different command functions.

16. The intelligent flashlight of claim 1, wherein said switch comprises more than one switch with each switch indicating a different command function recognizable by the microchip.

17. The intelligent flashlight of claim 1, wherein the at least one other function controlled by the microchip is selected from the group consisting of delayed shut off, oscillating power, dimming, intermittent code sequence, average current adjustment, and battery remaining charge functions.

09169395-100998
866007-5669760

18. An intelligent battery for use with an electrical device, the battery having positive and negative terminal ends and comprising:

a microchip embedded in the battery for controlling an on/off function and at least one other function of an electrical device.

19. The intelligent battery of claim 18, wherein the microchip comprises a control/reset means.

20. The intelligent battery of claim 18, wherein the microchip comprises a timing means.

21. The intelligent battery of claim 18, wherein the at least one other function controlled by the microchip is a delayed shut off function.

22. The intelligent battery of claim 18, wherein the at least one other function controlled by the microchip is an average current passed from the battery adjustment function.

23. The intelligent battery of claim 18, wherein the at least one other function controlled by the microchip is a power reduction function.

24. The intelligent battery of claim 18, wherein the at least one other function controlled by the microchip is an oscillating power function.

25. The intelligent battery of claim 18, wherein the at least one other function controlled by the microchip is an intermittent code sequence function.

26. The intelligent battery of claim 18, wherein the at least one other function controlled by the microchip is a determination of the charge remaining in the battery function.

27. The intelligent battery of claim 26, wherein the microchip is in communication with a means for indicating to an operator the amount of charge remaining in the battery.

28. A portable microchip device for use in serial connection with power source and an electrical device powered by said source, said electrical device having an input means for activating and deactivating said power source, said microchip comprising:

means for controlling the on/off function and at least one other function of the device upon receipt of a signal from said input means upon activation and deactivation of said input means.

29. The microchip device of claim 28, wherein the at least one other function is a power reduction function.

30. The microchip device of claim 28, wherein the at least one other function is an oscillating power function.

31. The microchip device of claim 28, wherein the at least one other function is a delayed power off function.

32. The microchip device of claim 28, wherein the at least one other function is a power adjusting function.

33. The microchip device of claim 28, wherein the at least one other function is an intermittent power function.

34. The microchip device of claim 28, wherein the microchip device is disc-shaped.

35. The microchip device of claim 28, wherein the at least one other function is selected from the group consisting of delayed power off, oscillating power, average current adjustment, intermittent power, dimming, and battery charge remaining functions.

36. An intelligent portable electrical device comprising:

a non-energy transferring MMI signal switch,

a microchip, and

a switch, the switch being in communication with the microchip and capable of transmitting a signal to the microchip that the switch has been activated or deactivated, wherein the microchip controls the on/off function and at least one other function of the device in response to the activation and deactivation signals received from the switch.

37. The electrical device of claim 36, wherein the other function is selected from the group consisting of delay power off, oscillating power, dimming, intermittent code sequence, average current adjustment, and battery remaining charge functions.

38. A battery comprising:

an energy storage section, a processor, and first and second terminal ends,

wherein the first terminal end is connected to said energy storage section,

the second terminal end is connected to the processor, and

the processor controls the connection of the second terminal end to the energy storage section.

39. An electrical device comprising:

a power supply, an activating/deactivating means, and a processor,

wherein the processor controls at least one function of the device in response to a signal received from the activating/deactivating means.

40. A flashlight comprising:

a light source, an energy storage means in communication with the light source, a switch means, and a processor means wherein said processor means controls the activation of the light source in response to signals received from the switch means.

ABSTRACT

09169395-100998

The present invention provides for a unique microchip or circuit which can, *inter alia*, handle both current conducting functions and man-machine-interface functions in an electrical device, for example, such as a flashlight. The man-machine-interface functions, according to the present invention, may be controlled by very low current signals, touch pads, carbon coated membrane type switches, or other low current type switches. These low current switches are smaller, more reliable, less costly, easier to seal, and less vulnerable to corrosion and oxidation than prior art switches. Moreover, since according to the present invention, the current conducting switch is controlled in an intelligent manner by the same microchip which provides the man-machine-interface functioning, significant costs savings and reliability are achieved by the invention.

The present invention, according to one embodiment, also provides a microchip or circuit which may be embedded into a power source, for example, a battery, that supplies intelligence to the same. As a result, and according to the invention, functions such as delayed switching, dimming, delayed automatic shut off and an intermittent activation may be realized in less intelligent prior art electrical devices. According to certain embodiments of the present invention, the inventive microchips or circuits of the present invention can, *inter alia*, adjust the average electrical current through a current switch, provide an "on" and "off" sequence which, in the case of a flashlight, can be determined by an operator and may represent either a flash code sequence or a simple on-off oscillation, delayed shut-off function, dimming function, provide indication of power strength, and


provide gradual oscillating current flow to lengthen the life of the operating switch and the battery, etc.

866007" 56E69F60

da\P\Post\B71403US\pat.app

86600T" 56E69T60

FIGURE 1



016995-10098





FIGURE 3



09169395-100998

86600T" 5669T60





FIGURE 5



86600T-56E9T60

FIGURE 6





FIGURE 7.



09169395-100998

09169395-109998

FIGURE 8A





FIGURE 8B



09169395-100998

0016395-10098
86600T-5669T60




FIGURE 9

86600T"56E69T60




FIGURE 10




FIGURE 11

09169395-100998




FIGURE 12




FIGURE 13

09169395-100998

09169395-100998




FIGURE 14

09169395-100998





FIGURE 15


09169395-100998



* Power Source 101 connected to microchip 103 as per circuit shown in Figure 4.

FIGURE 16

00160395-100998



* Power activated by closure of 102 from an open position.
FIGURE 17



UNITED STATES PATENT AND TRADEMARK OFFICE

Commissioner for Patents, Box PCT
United States Patent and Trademark Office
Washington, D.C. 20231
P. 190527M/R

09/806,860	BRUWER	F	P. 190527M/R
U.S. APPLICATION NO.	FIRST NAMED APPLICANT	ATTY. DOCKET NO.	

09/806860

5071

INTERNATIONAL APPLICATION NO. 09/00107

WILLIAM A BLAKE
JONES TULLAR & COOPER
PO BOX 2266 EADS STATION
ARLINGTON DC 22202

I.A. FILING DATE 07/18/99 PRIORITY DATE 07/09/98

07/19/01

DATE MAILED:

**NOTIFICATION OF ACCEPTANCE OF APPLICATION UNDER 35 U.S.C. 371
AND 37 CFR 1.494 OR 1.495**

1. The applicant is hereby advised that the United States Patent and Trademark Office in its capacity as ☐ a Designated Office (37 CFR 1.494), ☒ an Elected Office (37 CFR 1.495), has determined that the above-identified international application has met the requirements of 35 U.S.C. 371, and is **ACCEPTED** for national patentability examination in the United States Patent and Trademark Office.

2. The United States Application Number assigned to the application is shown above and the relevant dates are:

<u>02 July 01</u> DATE OF RECEIPT OF 35 U.S.C. 371(c)(1), (c)(2) and (c)(4) REQUIREMENTS	<u>02 July 01</u> DATE OF RECEIPT OF ALL 35 U.S.C. 371 REQUIREMENTS
--	---

A Filing Receipt (PTO-103X) will be issued for the present application in due course. **THE DATE APPEARING ON THE FILING RECEIPT AS THE "FILING DATE" IS THE DATE ON WHICH THE LAST OF THE 35 U.S.C. 371 REQUIREMENTS HAS BEEN RECEIVED IN THE OFFICE. THIS DATE IS SHOWN ABOVE.**
The filing date of the above-identified application is the international filing date of the international application (Article 11(3) and 35 U.S.C. 363). Once the Filing Receipt has been received, send all correspondence to the Group Art Unit designated thereon.

3. ☐ A request for immediate examination under 35 U.S.C. 371(f) was received on _____ and the application will be examined in turn.

4. The following items have been received:

- ☒ U.S. Basic National Fee.
- ☒ Copy of the international application.
- ☐ Translation of the international application into English.
- ☒ Oath or Declaration of inventors(s).
- ☐ Copy of Article 19 amendments. ☐ Translation of Article 19 amendments into English.
The Article 19 amendments ☐ have ☐ not been entered.
- ☒ The International Preliminary Examination Report in English and its Annexes, if any.
- ☒ Copy of the Annexes to the International Preliminary Examination Report (IPER).
☐ Translation of Annexes to the IPER into English.
The Annexes ☐ have ☐ not been entered.
- ☒ Preliminary amendment(s) filed 05 April 01 and 02 July 01
- ☐ Information Disclosure Statement(s) filed _____ and _____
- ☐ Assignment document.
- ☒ Power of Attorney and/or Change of Address.
- ☐ Substitute specification filed _____
- ☒ Indication of Small Entity Status.
- ☒ Priority Document.
- ☒ Copy of the International Search Report ☒ and copies of the references cited therein.
- ☐ Other:

Applicant is reminded that any communication to the United States Patent and Trademark Office must be mailed to the address given in the heading and include the U.S. application no. shown above (37 CFR 1.5).

Lamont Hunter, Paralegal

Telephone: 703 305-3686

THIS PAGE BLANK (USPTO)